

MULTI-USE LOGGER WITH DISPLAY



UTRED-16

USB External Probe Temperature Logger with Display

LogTag Recorders



The LogTag® UTRED-16 is an affordable & reliable USB temperature recorder, measures and stores real time temperature readings over a measurement range of -40°C to +99°C (-40°F to 210°F).

The LogTag® UTRED-16 comes with advanced temperature recorder features of 16,000 log memory and can be used with all external probes from the ST100 range, and the extension cable. It complies with relevant international standards for temperature monitoring devices, such as FCC, CE, IC and RCM.

Accessories



Glycol Buffer
Not Included



External Probe
Not Included. (Required)

Probes are available with a 1.5m or 3m cable.
E.g. ST100J-15 for 1.5m or ST100J-30 for 3m cable.

Compatible probes below:

ST100J	40mm tip length, ø3.2mm.
ST100K	65mm tip length, ø3.2mm.
ST100L	90mm tip length, ø3.2mm.
ST100S	30mm tip length, ø5mm.
ST100T	140mm tip length, ø5mm.
ST100H	Handled with 105mm tip length, ø5mm.
ST100B	Untipped (bare sensor).
STX50	5 Meter extension cable for ST10/ST100 sensors.

Features



Records temperature from -40°C to $+99^{\circ}\text{C}$.



Measure and store up to 16,000 time/temperature readings.



Up to 16,000 recordings - enough for 168 days at 15 minute logging.



Can be connected to any computer with a USB port. No interface cradle required.



Read current temperature and latest Min-Max temperature at a glance.



Fixed battery of 1 year storage, 2 years of normal use.



Display showing temperature and alarm status of up to six alarms.



Creates a comprehensive data file compatible with LogTag Analyzer operating software.



Automatic generation of a PDF report as a permanent record of the data.



Auto-pause function suspends alarm and statistic processing when the external sensor is unplugged.

Applications



Pharmaceuticals



Produce



Healthcare



Chemicals

Specifications

Product Model	UTRED-16F (Fixed Battery).
Sensor Measurement Range	-40°C to +99°C (-40°F to 210°F).
Operating Temperature Range	-30°C to +60°C (-22°F to +140°F).
Storage Temperature Range	0°C to +40°C (32°F to +104°F).
Rated Temperature Reading Resolution	Better than 0.1°C (0.2°F) for -30°C to +60°C (-22°F to +140°F). Better than 0.2°C (0.4°F) for -40°C to -30°C (-40°F to -22°F). Better than 0.5°C (0.9°F) for +60°C to +99°C (+140°F to +210°F). <i>LogTag Analyzer® currently displays to one decimal place of °C or °F. The native resolution is what is stored in the LogTag®.</i>
Rated Temperature Reading Accuracy	Better than ±0.5°C (±0.9°F) for -20°C to +40°C (-4°F to +104°F), typically ±0.3°C (0.6°F). Better than ±0.8°C (±1.4°F) for -40°C to -20°C (-40°F to -4°F), typically ±0.5°C (0.9°F). Better than ±0.8°C (±1.4°F) for +40°C to +70°C (+104°F to +158°F), typically ±0.7°C (1.3°F). Better than ±1.2°C (±2.2°F) for +70°C to +99°C (+158°F to +210°F), typically ±1°C (1.8°F).
Recording Capacity	16,129 temperature readings. 112 days @ 10min logging, 168 days @ 15min logging. Statistics memory (for display on LCD): Max/Min values and alarm duration values.
Sampling Interval	Configurable from 30 seconds to 18 hours.
Logging Start Options	Push button start or specific date & time. Optional start delay of up to 72 hours.
Recording Indication	"REC" symbol on LCD
Alarms	Three configurable upper and three configurable lower alarms.
Logging Start Options	Push button start or specific date & time. Optional start delay.
Download Time	Typically with full memory (16,129 readings) in less than 30 seconds from time of insertion to availability of PDF report. Typically less than 10 seconds from time of insertion to availability of LTD file in LogTag® Analyzer (if configured)
Environmental	IP61 (when vertically mounted or hung with USB dust-cap in place).
Power Source	CR2450 3V LiMnO ₂ (Fixed battery).
Battery Life	1 year storage, 2 years of normal use (based on 15 minute logging, download data monthly).
Real Time Clock	Built-in real time clock. Rated accuracy ±25ppm @ 25°C (equivalent to 2.5 seconds/day). Rated temperature coefficient is -0.034 ±0.006ppm/°C (i.e typically +/- 0.00294 seconds/day/°C).
Connection Interface	USB 2.0, A-type plug.
Software	PDF Reader, LogTag® Analyzer 3.1.9 or higher.
PDF Report	One page report with trip and alarm summary. Multi-page report with list of readings, including date and time.
Size	93mm(H) x 54.5mm(W) x 8.6mm(T) including protective USB cap.
Weight	39g.
Case Material	Polycarbonate.

