

On-the-go Data Logging now available.

The Verigo Pod RH multi-use logger records and wirelessly transmits temperature and relative humidity (RH) data to your smartphones and tablets. No cables or readers required! Simply download Verigo's app for iOS™ to your device and start using your Pod.

Users can configure their Pod by giving a customized name or scan the bar code, set temperature/humidity thresholds and adjust logging intervals.

During operation, users can see the instant readings, full data graphs and alerts on all Pods up to 40 meters away (130 ft).

For further analysis, use the SHARE function to email data in PDF or CSV format.

Cloud storage allows users to access information from anywhere via Verigo's secure Web App and view location points as well as generate PDF or CSV files for data analysis.

Quantity discounts available.
Call us for special pricing.

© 2015 Global Sensors, LLC
All rights reserved.

Verigo POD Wireless Humidity Logger

No more need for interface readers and cables!!!

Simply open the app on your smartphone and retrieve data up to 40 meters (130 ft) from the loggers.

Model PAO



Wirelessly read temperature and humidity in real-time on your iOS™ device.



Review and analyze data in the cloud with Verigo's Web App.

PRODUCT SPECIFICATIONS

PS#86

Temperature Measurement Range	-20°C to 60°C (-4°F to 140°F)
Temperature Accuracy	±0.4°C from -10 to 60°C ±0.72°F from 14 to 140°F ±0.6°C from -20 to -10°C ±1.1°F from -4 to 14°F
Temperature Resolution	0.01°C (0.018°F)
Temperature Response Time (T90)	Less than 20 min (in 0.1 m/s air flow)
Humidity Measurement Range	0% to 100% RH (non-condensing)
Humidity Accuracy	±3% RH from 0% to 80% RH ±4.5% RH from 80% to 100% RH
Humidity Resolution	± 0.03% RH
Humidity Sensor Hysteresis	± 1% RH
Transmission Range	Up to 40 meters (130 feet)
Memory	40,000 data points (temperature) 40,000 data points (RH)
Battery	Primary Lithium-ion (non-rechargeable) 1.5 – 5 years life
Shelf Life	7 years
Required Accessories	Device with iOS 7+ Verigo Mobile App
Unit Weight	30 grams (1.06 oz.)
Case	ABS
Dimensions	97 x 43 x 13 mm 3.8 x 1.7 x 0.5 in.
Certifications	FC CE Industry Canada
Compliance	CFR Title 21, 2011/65/EU, RoHS
Instructions	English, Spanish and French

